


## Laser Tag Label Materials


Laser Tags are durable, laser printable labels for applications requiring clear, crisp legibility. The labels come on 216 mm x 279 mm sheets and are printable using HellermannTyton TagPrint Pro software and a standard laser printer. Specially designed adhesives and materials are used for the Laser Tags, ensuring that the labels will not curl, change colour, or jam laser printers. Laser Tags are available in die-cut on 216 mm x 279 mm polyester sheets.



Label Material	105 Material <span style="border: 1px solid black; border-radius: 50%; padding: 2px;">RoHS</span>	788 Material <span style="border: 1px solid black; border-radius: 50%; padding: 2px;">RoHS</span>	788C Material <span style="border: 1px solid black; border-radius: 50%; padding: 2px;">RoHS</span>	789 Material <span style="border: 1px solid black; border-radius: 50%; padding: 2px;">RoHS</span>
<b>Material Name</b>	Self-Laminating Laser Polyester	White Laser Polyester	Clear Laser Polyester	White Laser Polyester
<b>Printer(s)</b>	Laser	Laser	Laser	Laser
<b>Topcoat</b>	Specially formulated for superb ink anchorage	Specially formulated for superb toner anchorage for most laser printers	Specially formulated for superb toner anchorage for most laser printers	Specially formulated for superb ink anchorage
<b>Liner</b>	82#	68#	68#	90#
<b>Temperature Range</b>	-40°C to +149°C	-40°C to +92°C	-40°C to +92°C	-40°C to +149°C
<b>Adhesive Type</b>	Permanent pressure sensitive acrylic	Permanent pressure sensitive acrylic	Permanent pressure sensitive acrylic	Permanent pressure sensitive acrylic
<b>Application</b>	Excellent for on-the-job wire marking. Ideal for flat ribbon cable, machine tool and underground wiring. Smallest diameter is 3.81 mm	Excellent for general purpose component or panel marking. Bar code printable	Excellent for general purpose component or panel marking. Bar code printable	For flat labelling applications that require solvent or high temperature resistance. Bar code printable. Can be used to mark electronics and printed circuit boards
<b>Certifications</b>				
<b>Outdoor Durability</b>	N/A	1 year	1 year	2 years
<b>Chemical Resistance</b>	Good for most petroleum based solvents and lower aliphatic alcohols. not good for most esters and ketones. Water resistant.	Applied labels will be resistant to water, mild acids, alkalis, salts and most petroleum based solvents, oils, greases, aliphatic solvent such as kerosene, keptane and reference fuel	Applied labels will be resistant to water, mild acids, alkalis, salts and most petroleum based solvents, oils, greases, aliphatic solvent such as kerosene, keptane and reference fuel	Applied labels will be resistant to water, mild acids, alkalis, salts and most petroleum based solvents, oils, greases, aliphatic solvent such as kerosene, keptane and reference fuel

## Laser Tag Labels

HellermannTyton's Laser Tag labels are used for component marking.



Technical Table

Code	Type	Width (W) mm	Height (H) mm	Labels per Row	Labels per Column	Labels per Sheet	Pkg. Qty.
<b>788 Material</b>							
TAGPP1-788	TAGPP1	15.87	7.87	12	30	360	1000
TAGPP2-788	TAGPP2	16.7	8.38	12	30	360	1000
TAG62L-788	TAG62L	31.75	9.52	5	25	125	1000
TAG61L-788	TAG61L	66.67	25.4	3	10	30	7500
TAG60L-788	TAG60L	71.88	38.1	3	7	21	5250
TAG59L-788	TAG59L	101.60	38.1	2	7	14	3500
TAG58L-788	TAG58L	101.60	50.8	2	5	10	2500
TAG56L-788	TAG56L	101.60	84.5	2	3	6	1500
TAG57L-788	TAG57L	107.90	69.8	2	4	8	2000
TAG55L-789	TAG55L	107.90	139.70	2	2	4	500
TAG54L-788	TAG54L	215.90	139.70	1	2	2	500
TAG53L-788	TAG53L	215.90	274.6	1	1	1	250
<b>788C Material</b>							
TAGPP1-788C	TAGPP1	15.87	7.87	12	30	360	1000
TAGPP2-788C	TAGPP2	16.7	8.38	12	30	360	1000
<b>789 Material</b>							
TAG11L-789	TAG11L	16.50	5.08	10	48	480	5000
TAG13L-789	TAG13L	19.00	6.35	8	39	312	5000
TAG14L-789	TAG14L	25.40	9.52	7	25	175	5000
TAG15L-789	TAG15L	25.40	12.70	7	19	133	5000
TAG96L-789	TAG96L	47.62	6.35	4	36	144	1000
TAG69L-789	TAG69L	50.8	6.98	4	35	140	5000
TAG67L-789	TAG67L	73	9.52	2	25	50	1000
TAG66L-789	TAG66L	91.4	9.52	2	25	50	1000
TAG68L-789	TAG68L	96.5	6.98	2	35	70	2500
TAG45L-789	TAG45L	101.60	20.32	2	12	24	5000
<b>Cardstock Material</b>							
TAGPHONE	TAGPHONE	44.45	9.52	4	21	84	1000

Dimensions are approximate and subject to technical changes. Use **Part No.** for ordering and **Type** for specification purposes.